

# DIALANDO®

## Swiss Military Hanowa men's watch 06-5230.7.02.007 Specifications



BEISPIELBOX

BUY NOW

This document contains all the specifications for the Swiss Military Hanowa Swiss Recruit II 06-5230.7.02.007 men's watch. We at the **DIALANDO® watch store** offer a large selection of authentic watches from the best watch brands in the world. <https://www.dialando.lv/>

### PRODUCT INFORMATION

|                  |                       |
|------------------|-----------------------|
| EAN              | 7620958000278         |
| Gender           | Men                   |
| Brand            | Swiss Military Hanowa |
| Collection       | Swiss Recruit II      |
| Warranty [years] | 2                     |

### PRODUCT EXECUTION

|               |                               |
|---------------|-------------------------------|
| Display Type  | Analogue                      |
| Movement type | Quartz (Battery)              |
| Movement Name | 515 AIG 2 / Ronda             |
| Functions     | Second / Minute / Date / Hour |

### MEASURES

|                               |     |
|-------------------------------|-----|
| Case width [mm]               | 39  |
| Case thickness [mm]           | 10  |
| Lug width [mm]                | 20  |
| Max. wrist circumference [mm] | 210 |

### MATERIAL & COLOUR

|                    |                   |
|--------------------|-------------------|
| Strap Material     | Stainless steel   |
| Strap Colour       | Gold              |
| Case Material      | Stainless steel   |
| Case Colour        | Gold              |
| Case Surface       | Polished / Matted |
| Colour of the dial | Black             |
| Glass              | Sapphire glass    |

### DETAILS

|                 |                                   |
|-----------------|-----------------------------------|
| Bezel           | Fixed                             |
| Case Bottom     | Stainless steel bottom (screwed)  |
| Clasp           | Folding clasp                     |
| Lighting        | Luminous hands / Luminous indexes |
| Water resistant | 5 ATM                             |